



URSA XPS D N-III-PZ I

TWINS

Thickness d_N [mm]

140

Thermal conductivity

λ_D [W/(m*K)]

0,033

Thermal resistance

R_D [m²*K/W]

4,20

Reaction to fire

E



URSA XPS D N-III-PZ TWINS

DoP-No: 49XPSDN3PZTW19011

<http://dop.ursa-insulation.com>

EN 13164:2012+A1:2015

Factory made extruded polystyrene (XPS) foam products

Thermal Insulation for Buildings

T1-CS(10\Y)300-DS(70,90)-DLT(2)5-TR200

URSA Deutschland GmbH, Carl-Friedrich-Benz-Str. 46-48, 04509 Delitzsch

www.ursa.de

/EU/ -T1-CS(10\Y)300-DS(70,90)-DLT(2)5-TR200

/DE/ Anwendung nach DIN 4108-10: DEO-dh,DI,WAP,WI

/CH/ $\lambda_D = 0,033$ [W/(m*K)] gemäß DIN 4108-4: 0,034 [W/(m*K)]

/AT/ $\lambda_D = 0,033$ [W/(m*K)] gemäß SIA 279


RF 3(cr)

/AT/ Produktart: XPS-R nach ÖNORM B6000



011-7D094

2139961



8

435062

266927

Q-8B01-L6

13200207

Length [mm]

1250

Width [mm]

600

Piece(s)

3

Surface [m²]

2,250

Edge



bonus



holsystem