



URSA XPS D N-III-PZ I

Thickness d_N [mm]	Thermal conductivity λ_D [W/(m ² K)]	Thermal resistance R_D [m ² K/W]	Reaction to fire
30	0,033	0,90	E



URSA XPS D N-III-PZ

DoP-No: 49XPSDN3PZ19101

<http://dop.ursa-insulation.com>

EN 13164:2012+A1:2015

Factory made extruded polystyrene (XPS) foam products

Thermal Insulation for Buildings

T1-CS(10Y)200-DS(70,90)-DLT(2)5-TR200

URSA Deutschland GmbH, Carl-Friedrich-Benz-Str. 46-48, 04509 Delitzsch

www.ursa.de

/EU/ -T1-CS(10Y)200-DS(70,90)-DLT(2)5-TR200

/DE/ Anwendung nach DIN 4108-10: DEO-dm,DI,WI,WAP


Bemessungswert der Wärmeleitfähigkeit gemäss DIN 4108-4: 0,034 [W/(m²K)]

/AT/ Produktart: XPS-R nach ÖNORM B6000



011-7D077

2127040



8 435062 213204

Q-8B01-L6 15201012

Length [mm]

1250

x

Width [mm]

600

Piece(s)

14

Surface [m²]

10,500

Edge



bonus



holsystem